



429.00 EUR  
 incl. 19% VAT, plus [shipping](#)

- INTEL® Braswell--D J3160 SOC Chipset
- Onboard INTEL® Braswell-D J3160 2.24GHz QC CPU
- On board 4G DDR3L 1600 Memory
- Support DirectX 12 3D Graphics Acceleration
- Integrated HD Audio CODEC
- Support 2\*PCI Express Gigabit LAN
- Support 1\*DP Port and 2\*HDMI Ports
- Support 3\*USB3.0 Ports
- Support 1\*M-SATA Socket (Full size)
- Support 2\*Mini PCI-E Socket (1\*Full size +1\* Half size)
- Support Vibration protection function
- Support Thunder Protection Function
- 25mm thin, slice design

|             |                     |                              |
|-------------|---------------------|------------------------------|
| <b>Case</b> | Panel Material      | Aluminum                     |
|             | Color               | Option                       |
|             | Coating Requirement | Spray Paint + Anode          |
|             | Cooling Mode        | Fan less Fully sealed design |

|                             |                |                                                                     |
|-----------------------------|----------------|---------------------------------------------------------------------|
| <b>System Specification</b> | Form Factor    | uITX                                                                |
|                             | Processor      | INTEL® Braswell-D J3160 2.24GHZ/QC                                  |
|                             | GPU            | INTEL® HD Graphics 400                                              |
|                             | System Chipset | INTEL® Braswell-D J3160 (SOC)                                       |
|                             | System Memory  | 4G/DDR3L                                                            |
|                             | BIOS           | 64MB SPI Flash ROM                                                  |
|                             | Ethernet       | 2*Realtek® RTL8111G Gigabit LAN                                     |
|                             | Audio          | Realtek® ALC662 HD Audio                                            |
|                             | Storage        | 1* M-SATA connector                                                 |
|                             | WIFI Module    | Option                                                              |
|                             | Optical Device | N/A                                                                 |
|                             | Expansion      | 2*PCI-E mini card for WLAN                                          |
|                             | Display Output | 1*DP+2*HDMI                                                         |
|                             | Display        | Three Independent Displays                                          |
|                             | Resolution     | 3840x2160@ 30Hz ■ 2560x1600@60Hz                                    |
|                             | I.O Port       | 3*USB3.0 ■ 1*Line-out ■ 1*MIC ■ 2*RJ45 ■ 1*Power Button ■ 1*DC-Jack |
|                             | Power Adapter  | DC-IN (9~24V)                                                       |
|                             | OS Support     | Windows 7/8.1/10                                                    |
|                             | Temperature    | Operating ■ -10 ~ +60 ■                                             |
|                             | Humidity       | 20%~90% (non condensing)                                            |
|                             | Dimension      | 148.0mm*116.0mm*25.0mm                                              |
|                             | Certification  | FCC CE (Option)                                                     |